


### 1 Product Description

The MTL200QA supports all kinds of inductive position sensors.

The MTL200QA is a IC which can process all kinds of inductive position sensor signals. It integrates oscillator & LDO & temperature sensor & signal processing module.

The MTL200QA provides QFN2\*2-14L for surface mount (MSL2), RoHS compliant.



### 2 Features

- 3.6~5.5V Operating VCC Range
- Sampling Frequency: Up to 4KHz
- Oscillator Frequency: Up to 5MHz
- -40°C~105°C Operating Temperature
- Input Signal Threshold Adjustment
- Package Option: QFN2\*2
- RoHS Compliant: (EU)2015/863

### 3 Product Overview of MTL200QA

Part No.	Description
MTL200QA	QFN2*2-14L, tape & reel (3000pcs/bag)

### 4 Applications

- Inductive Position Sensor

### 5. Pin Configuration and Functions

No.	Name	Description
1	VCC	Power Supply
2	CTRL	Control Pin
3	RHY	Hysteresis Setting
4	RDI	Distance Setting
5	LC	LC Oscillator
6	NC	
7	Out	Digital Output
8	NC	
9	Vrefer In	Reference In
10	ANA Out	Analog Out
11	Temp Out	Temp. Out
12	GND	Ground
13	NC	
14	NC	




Figure.1 Pin Configuration & Functions

## Table of Contents

1	Product Description.....	1
2	Features.....	1
3	Product Overview of MTL200QA .....	1
4	Applications.....	1
5	Pin Configuration and Functions.....	1
6	Functional Block Diagram .....	3
7	Electrical and Magnetic Characteristics.....	3
	7.1 Absolute Maximum Ratings.....	3
	7.2 ESD Ratings.....	3
	7.3 Electrical Specifications.....	4
8	Typical Application Circuit.....	5
9	Characteristic Performance.....	6
10	Package Material Information.....	7
	10.1 QFN2*2 14L Package Information.....	7
11	Copy Rights and Disclaimer.....	8

## Reversion History

1	1.0 Version	Originally Version
2	1.1 Version	Update the Product Overview

## 6 Functional Block Diagram




Figure.2 Functional Block Diagram

## 7 Electrical and Magnetic Characteristics

### 7.1 Absolute Maximum Ratings

Absolute maximum ratings are limited values to be applied individually, and beyond which the serviceability of the circuit may be impaired. Functional operability is not necessarily implied. Exposure to absolute maximum rating conditions for an extended period of time may affect device reliability. All voltages listed are referenced to GND.

Symbol	Parameters	Min	Max	Units
V <sub>CC</sub>	Supply Voltage	-	7	V
V <sub>OUT</sub>	Output Voltage	-	7	V
V <sub>RDI</sub> , V <sub>RHY</sub> , V <sub>ANA_OUT</sub> , V <sub>TEMP</sub> , V <sub>CTRL</sub> , V <sub>REFER</sub>	I/O pin Voltage	-	7	V
V <sub>LC</sub>	LC pin Voltage	-7	7	V
I <sub>OUT</sub>	Continuous Output Current	-10	10	mA
T <sub>A</sub>	Operating Ambient Temperature	-40	105	°C
T <sub>S</sub>	Storage Temperature	-50	150	°C

### 7.2 ESD Ratings

Symbol	Parameters	Reference	Values	Unit
V <sub>ESD</sub>	Human-body model (HBM)	AEC-Q100-002	2000	V
	Charged-device model (CDM)	AEC-Q100-011	1500	V


### 7.3 Electrical Specifications

At  $T_A = -40 \sim 105 \text{ }^\circ\text{C}$ ,  $V_{CC} = 3.6\text{V} \sim 5.5\text{V}$  (unless otherwise specified)


Symbol	Parameters	Test Condition	Min	Typ	Max	Unit
V <sub>CC</sub>	Supply Voltage		3.6	-	5.5	V
I <sub>CC</sub>	Supply Current	V <sub>CC</sub> =5V	-	-	2	mA
R <sub>DI</sub>	R <sub>DI</sub> Resistance		-	-	R <sub>p</sub> of the LC Coil	Ohm
R <sub>HY</sub>	R <sub>HY</sub> Resistance	Series Application	-	R <sub>DI</sub> /30	-	Ohm
		Parallel Application	-	40*R <sub>DI</sub>	-	Ohm
V <sub>SAT</sub>	Output Saturation Voltage	I <sub>OUT</sub> =5mA; Output On	-	-	0.5	V
I <sub>OFF</sub>	Output Leakage Current	Output Off	-	-	1	uA
F <sub>Sampling</sub>	Sampling Frequency	V <sub>CC</sub> =5V Target @ ½ DOP (Max)	-	4	-	KHz
DOP	Operation Point of Detection (Can be adjusted through R <sub>DI</sub> )	The Ratio of the Coil's Diameter (Depends on the performance of the Coil)	50	-	150	%
D <sub>HYST</sub>	Detection Hysteresis (Can be adjusted through R <sub>HY</sub> )	The Ratio of the Detection Distance	1	-	20	%
T <sub>R</sub>	Output Rise Time	R <sub>L</sub> =10KΩ; C <sub>L</sub> =20pf;	-	-	1	us
T <sub>F</sub>	Output Fall Time	R <sub>L</sub> =10KΩ; C <sub>L</sub> =20pf;	-	-	1	us
T <sub>PO</sub>	Power on Time	Without the Settling Time of the Coil	-	8	15	ms
PA	Position Accuracy	1 sigma of Q Value < 1.5%	-10	-	+10	%
RA	Repetition Accuracy		-	-	3	%
F <sub>osc</sub>	Oscillator Frequency		-	-	5	MHz
A <sub>osc</sub>	Oscillator Amplitude	Depends on the R <sub>p</sub> & R <sub>DI</sub> of the the Coil		3.6	-	V <sub>pp</sub>
ANA <sub>OUT</sub>	ANA Out	Depends on the R <sub>p</sub> & R <sub>DI</sub> of the the Coil	0.70		3.0	V
TEMP <sub>OUT</sub>	TEMP. Out	-40°C ~ 110°C	0.75		1.5	V

## 8 Typical Application Circuit


This typical application circuit provides user integration solution of the inductive position sensor. MTL200QA integrates oscillator & LDO & temperature sensor & signal processing module. MT5201DT integrates LDO & driver & circuit protection module (short circuit protection/over current protection/reversed power supply protection/reversed output protection/out Temp. protection). Small footprint (MTL200QA: 2mm\*2mm & MT5201DT: 2mm\*3mm) makes user easily cover the small size of the inductive position sensor.




**Figure.3** Series Application of RDI & RHY (MTL200QA + MT5201DT) Normal Open Connection



**Figure.4** Series Application of RDI & RHY (MTL200QA + MT5201DT) Normal Close Connection



**Figure.5** Parallel Application of RDI & RHY (MTL200QA + MT5201DT) Normal Open Connection



**Figure.6** Parallel Application of RDI & RHY (MTL200QA + MT5201DT) Normal Close Connection

MTL200QA Out		VN	VP	NPN Out	PNP Out	LED
To VN (Figure.3 & Figure.5) (NO Connection)	Off	VDD	VDD	High	Low	Off
To VN (Figure.3 & Figure.5) (NO Connection)	On	GND	VDD	Low	High	On
To VP (Figure.4 & Figure.6) (NC Connection)	Off	GND	VDD	Low	High	On
To VP (Figure.4 & Figure.6) (NC Connection)	On	GND	GND	High	Low	Off

## 9 Characteristic Performance




Figure.7 Icc vs, Temperature @ Vcc=5V




Figure.8 Icc vs, Vcc @ Temperature @ 25°C




Figure.9 VTemp Out vs, Temperature @ Vcc=5V




Figure.10 VTemp Out vs, Vcc @ Temperature @ 25°C

## 10 Package Material Information (For Reference Only – Not for Tooling Use)

### 10.1 QFN2\*2 14L Package Information




Figure.11 QFN2\*2 14L (Thin Outline) Chip Marking Spec




Figure.12 QFN2\*2 14L (Thin Outline) Package Drawing

Symbol	Dimensions in Millimeters		Dimensions in Inches	
	Min	Max	Min	Max
A	0.500	0.600	0.020	0.024
A1	0.000	0.050	0.000	0.002
A3	0.152 TYP		0.006 TYP	
D	1.900	2.100	0.075	0.083
E	1.900	2.100	0.075	0.083
D1	0.900	1.100	0.035	0.043
E1	0.900	1.100	0.035	0.043
b	0.150	0.250	0.006	0.010
e	0.400 TYP		0.016 TYP	
e1	0.450 TYP		0.018 TYP	
K	0.240 TYP		0.009 TYP	
L	0.184	0.336	0.007	0.013
L1	0.175	0.327	0.007	0.013

## 11 Copy Rights and Disclaimer

1. This document may not be reproduced or duplicated, in any form, in whole or in part without prior written consent of MagnTek . Copyrights © 2022, MagnTek Incorporated.
2. MagnTek reserves the right to make changes to the information published in this document at anytime without notice.
3. MagnTek' s products are limited for use in normal commercial applications. MagnTek' s products are not to be used in any device or system, including but not limited to medical life support equipment and system.

For the latest version of this document, please visit our website: [www.magntek.com.cn](http://www.magntek.com.cn)